



NATIONAL TYPE EVALUATION PROGRAM

Certificate of Conformance
for Weighing and Measuring Devices

For:

Multiple Dimension Measuring Device
Model: cubetape 190 MFT, cubetape 190 SPU
cubetape 190 MPU
Maximum: 108 inches
Minimum: 1.2 inches
 d_{min} : 0.1 inch
Software Version: V2.02.15 or higher

Submitted By:

Parcel Tools PTY Limited
PO Box 5178
Greenwich, NSW 2065 Australia
Tel: +61 439 892 468
Contact: Tony Bauer
Email: tbauer@cubical.com
Web site: www.cubetape.com

Standard Features and Options

Standard Features:

- USB Communication Port
- Bluetooth communications (BT-HID; BT-SPP)
- 1D barcode scanner (Models: MFT, MPU)

Dimensioning Designation:

Dimensions	d	Minimum	Maximum
Length	0.1 in	1.2 in	108 in
Width	0.1 in	1.2 in	108 in
Height	0.1 in	1.2 in	108 in

Temperature Range: -10 °C to 40 °C (14 °F to 104 °F)

This device was evaluated under the National Type Evaluation Program and was found to comply with the applicable technical requirements of "NIST Handbook 44: Specifications, Tolerances and Other Technical Requirements for Weighing and Measuring Devices." Evaluation results and device characteristics necessary for inspection and use in commerce are on the following pages.

Jerry Buendel
Chairman, NCWM, Inc.

Ronald Hayes
Committee Chair, National Type Evaluation Program Committee
Issued: March 17, 2016

1135 M Street, Suite 110 / Lincoln, Nebraska 68508

The National Conference on Weights and Measures (NCWM) does not approve, recommend or endorse any proprietary product or material, either as a single item or as a class or group. Results shall not be used in advertising or sales promotion to indicate explicit or implicit endorsement of the product or material by the NCWM.



Parcel Tools PTY Limited

Multiple Dimension Measuring Device / cubetape 190 MFT, cubetape 190 SPU & cubetape 190 MPU

Application: The cubetape 190 are used to calculate the dimensions of cuboidal shaped objects. Models with an integrated barcode scanner also are used retrieve and record data found in barcodes. The measuring mechanisms and accuracy of the models are identical.

Identification: The required information appears on a self- adhesive foil badge. With the foil badge, “void” is visible if an attempt to remove the label is made. During power up the NTEP CC & serial number is displayed.

Sealing: The cubetape 190 have no sealable parameters.

Operation: The cubetape 190 works by stretching the tape tip to one end of the object then align the tape stop with the other end of object. Measure and record the length dimension, then repeat for width and height dimensions. Data can be transmitted to host system via Bluetooth and USB.

Test Conditions: For the purpose of this evaluation, a model cubetape 190 MFT was submitted for evaluation. The emphasis of the evaluation was on device design, operation, markings, performance, and compliance with influence factor requirements. Several measurements were performed near maximum, near minimum, and near mid-range for the range listed. Several measurements were made via Bluetooth. The device was tested over a temperature range of -10 °C to 40 °C (14 °F to 104 °F).

NOTE: This Certificate is issued as a provisional NTEP Certificate of Conformance (CC). This evaluation is based on the current draft checklist, procedures and technical policy contained in NCWM Publication 14 for this device type. When work on the NCWM Publication 14 section for this device is completed, the test report and this NTEP CC will be reviewed. If all current requirements have been met by this evaluation, the provisional status will be removed.

Evaluated By: M. Kelley (OH)

Type Evaluation Criteria Used: *NIST Handbook 44 Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices*, 2016 Edition. *NCWM Publication 14 Weighing Devices*, 2016 Edition.

Conclusion: The results of the evaluation and information provided by the manufacturer indicate the device complies with applicable requirements.

Information Reviewed By: J. Truex (NCWM)

Examples of Device:

